「	<u>-</u> 71[7		
i 			
i 		нов	
i 			
1			
	1111		
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL
		BACK PANEL	FRONT PANEL







CHECK LIST
Reference the "Prepress Tips" page from our "Developer's Spec Kit" (available on our web site).

COLORS

Use only Process colors (CMYK) and/or Pantone spot colors from the "Pantone Formula Guide SOLID". (Note: there is a set-up fee for each Pantone color used. If you want to print with Pantone colors, please call for a custom quote.)

Provide 1/4 - 1/2 inch bleed on all edges. ("Bleed" is the part of the artwork which extends past the template cut line.)